

WASTE WATER TREATMENT

HELIX DRIVE

THE ECCENTRIC SCREW PUMPS FOR MEDIA WITH LOW AND HIGH VISCOSITY

> MAGNUM LEE/LEC

> MAGNUM ESPH/CSPH

> HELIX DRIVE

> MAGNUM SX





ΕN

WWW.BAUER-AT.COM

HELIX Drive

The Eccentric Screw Pumps with exceptional performance

Characteristics:

- Abrasion resistant, hardened smooth-running cupped rotors made of tough toolsteel– manufactured by BAUER with a special technology and absolutely break-proof
- Thermally optimized bearing for continuous operation
- Mechanical seal running in oil bath
- Large dimensioned intake and pressure connections to reduce plugging
- Access eye in intake housing
- Robust, permanently lubricated cardan joints
- Compact footprint
- Chassis designed for quick and safe mounting
- Quiet operation
- Easy to maintain
- Self priming

Permanently lubricated cardan joints beneath wearfree, highly tear-resistant Elastopal sleeves

Housing made of hot dip galvanised steel

Unique rotor

The low friction hollow rotor-the key component of every eccentric screw pump-is manufactured in a unique special process in the BAUER factory and is absolutely break-proof.

Longer durability

Tough tool steel and a consistent wall thickness of 8 mm prevent heat accumulation and stress cracks. The special coating applied makes for a tough and smooth surface. This process also ensures a longer life of the stator rubber, as the smooth rotor surface causes considerably less abrasion.

Exceptional smoothness

The light weight of the low friction hollow rotor guarantees consistent running smoothness in all speed ranges.

Driveshaft with oil bath bearing and mechanical seal Abrasion-resistant, hardened low friction hollow rotor made of tough tool steel

the intake housing

Access eye in

Non-swelling stator made of special rubber compound



Applications:

Dosing

Feeding

Flushing

Bringing in

Intertank transfer

Eccentric screw pump with motor driveideal for stationary use in both agricultural and industrial applications.

For media with low and high viscosity:

- Thick slurry
- Draff
- Liquid manureSewage sludge
- Molasses
- Potato pulp

Bog

- Starch
- Spent grains
- starchetc.
- = etc.

HELIX Eccentric Screw Pumps


High quality and reliability


In House factory production guarantees both reliable and immediate availability of consistently high-quality spare parts.



Extensive accessories such as:

- Stone catcher in form of a box or can
- Aspiration mouth with integrated stone catcher
- Drum filling station with adjustable discharge pipe
 All components for suc-
- tion and pressure lines





Technical Data

Pump type	Performance kW	Max. pressure in m	Flow rate max. m³/h	Flange suction side DN	Flange pressure side DN	Dimensions mm A x B
HELIXDRIVE 553	5,5	30	38	150	125	1850 x 400
HELIXDRIVE 556	5,5	60	15	150	125	1745 x 400
HELIXDRIVE 753	7,5	30	48	150	125	1873 x 400
HELIXDRIVE 756	7,5	60	18	150	125	1850 x 400
HELIXDRIVE 1103	11	30	65	150	125	1868 x 400
HELIXDRIVE 1106	11	60	35	150	125	1950 x 400

Rated power with water



PRODUCTS FROM OUR SLURRY PROGRAM



Tractor mixer



MAGNUM LEE/LEC Long shaft pump



MSXH Submersible motor mixer



MAGNUM SM Thick matter pump gear unit design



SEPARATOR Press screw separator for solid-liquid separation



MAGNUM CSPH Submersible motor pump gear unit design



SEPARATOR PLUG & PLAY System for portable slurry separation



HELIX DRIVE Eccentric screw pump



MAGNUM SX Thick matter pump gear and pedestal pump



Slurry tankers and polytanker Different tanker types for every requirement



Trailing hose applicator Modular system for all types of tankers



Slurry injector Innovative spreading technology

Your dealer

Röhren- und Pumpenwerk BAUER GmbH

- 8570 Voitsberg/Austria
- **T** +43 3142 200-0 **F** +43 3142 200-320/-340
- M sales@bauer-at.com
- W www.bauer-at.com
- EAUER QUALITYAND INNOVATION 1930

no-sun.com